

Alucast Circular Covers



Overview



APPLICATIONS

- Monitoring wells
- Inclinometer boreholes
- Piezometers
- Borehole rod extensometers

FEATURES

- Water resistant
- Labelled for extra security
- H-20 rated
- Lockable

Alucast water resistant circular covers offer lightweight, high security closure for installation within petrol forecourts or similar industrial environments.

The body and lid are made from heavy aluminium, ribbed for maximum load bearing capacity and tested to H-20 rating. They can be installed easily into either a pre-drilled circular hole or concreted into grade. They are water resistant due to the internal gasket sealing ring.

Fitted with counter sunk stainless steel locking screws and O-rings, which can be undone and re-locked easily, they offer a simple and secure locking device for groundwater monitoring wells.

They are marked 'Monitoring Well DO NOT FILL' for clear identification and to avoid any unauthorised access.

SPECIFICATIONS

Nominal Size (inch)	Flange Diameter (mm)	Flange Thickness (mm)	Skirt Diameter (mm)	Height Clear (mm)	Open Aperture (mm)	Weight (kg)
6	150	22	137	175	90	1.46
8	195	24	165	225	110	2.67
10	245	22	220	325	155	4.5



Geosense Ltd, Nova House, Rougham Industrial Estate, Rougham, Bury St Edmunds, Suffolk IP30 9ND, England

www.geosense.co.uk e sales@geosense.co.uk
t+44(0)1359 270457