

Borehole Fill Material

Grout Mix





Grout Mix is a pre-blended powder mixture of premium grade high quality sodium carbonate activated Bentonite powder and Ordinary Portland Cement (CEM 1) in a ratio of 2:1.

PACKAGING: 25kg paper bags, 40 bags per pallet.

APPLICATIONS

Borehole sealing

Grouting

Isolating instrumentation and sampling zones

FEATURES

Easy to use

Consistent mix quality

Easy to mix

High strength

Stable suspension

Rapid build up of viscosity

Can be used with traditional mixing equipment

Suitable for immediate use after mixing

Cement to BS EN 197-1 CEM 1

25kg bags

PROPERTIES

	BENTONITE	CEMENT		
Colour	Light yellowish grey	Light grey		
Odour	None	None		
рН	8.5-10	12-14		
Specific Gravity	800 - 1100kg/m³	1400kg/m³		
Moisture Content	12%	<5%		
% by weight passing BS410 150 μ sieve	min 95%	min 95%		
MIXING				
Litres/water per bag	30	35	40	50
Water/solid ratio	1.2	1.4	1.6	2
Water density kg/m³	1340	1323	1315	1211
Yield per bag (litres)	32.8	41.1	50	70.6

Geosense Ltd, Nova House, Rougham Industrial Estate, Rougham, Bury St Edmunds, Suffolk IP30 9ND, England www.geosense.co.uk e sales@geosense.co.uk t +44(0)1359 270457