

Borehole Fill Material

Cement



Ordinary Portland Cement (OPC) can be mixed with ballast, sand and gravel for concreting or, together with Bentonite, for grouting.

It is manufactured to comply with the requirements of BS EN 197-1 CEM I Portland cement strength class 42.5/52.5N. CEM I PC is CE Marked in accordance with Regulation 305/2011/ EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), which provides independent third-party certification of product conformity.

Supplied in 25Kg paper bags.

APPLICATIONS

Concrete boreholes

Concrete backfill

Grouting

FEATURES

Made to B.S E.N 197-1 42.5 R

CEM 1 grade

42.5 MPa strength after 28 days

HEALTH & SAFETY

Cement is irritating to eyes, respiratory system and skin. Keep out of the reach of children.

Avoid contact with the skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Wear suitable protective clothing.



Geosense Ltd, Nova House, Rougham Industrial Estate, Rougham, Bury St Edmunds, Suffolk IP30 9ND, England

www.geosense.co.uk e sales@geosense.co.uk t +44(0)1359 270457