



#### APPLICATIONS

- Standpipe Piezometers
- Groundwater monitoring wells
- Dewatering wells

#### FEATURES

- Easy to install
- Filter to suit soil conditions
- Drill smaller holes

GeoFilters control the ingress of fines and eliminates the need for additional filter material within the borehole.

They are made up of a woven synthetic filter material that covers the outside of slotted or perforated pipe and an outer protective cover which is secured either end by adhesive or non-adhesive fixing.

#### Geonet

Geonet is a high tensile EVA sleeve which protects the GeoFilter during transport and installation.

- High tensile strength
- High abrasion resistance
- Range of sizes from 19-400mm

#### Georap

A woven geotextile which provides filtration down to 150 microns, suitable for fine soils

- Pore size ranges from 150 - 250 microns
- Diameters from 19 to 400 mm

#### Geosock

A knitted polyester filter sock which provides filtration down to 300 microns suitable for medium soils.

- 300 or 450 micron pore size
- Diameters from 50 to 400 mm

# GeoFilter

## GEORAP

	Standard	GR150	GR250
Pore size 90% finer than (microns)	EN ISO 12956	180	270
Tensile strength (kN/m)MD	EN 10319	12	22
Tensile strength (kN/m)CD	EN 10319	12	21
CBR puncture resistance (N)	EN ISO 12236	1800	2800
Water permeability (x 10 <sup>-3</sup> ) m/s	EN ISO 11058	18	20
Material	100% Polypropylene		
Effect of UV light	All UV stabilised		

## GEO SOCK

	Standard	GS300 (up to 63 mm OD)	GS450(90 to 400mm OD)
Pore size 90% finer than (microns)	EN ISO 12956	300	450
Tensile strength (kN/m)	EN 10319	12	22
Puncture resistance (N)	ASTM D6241-04	1000	1000
Water permeability (x 10 <sup>-3</sup> ) m/s	EN ISO 11058	28	30
Material	All 100% Polyester		



Geosense Ltd, Nova House, Rougham Industrial Estate, Rougham, Bury St Edmunds, Suffolk IP30 9ND, England

[www.geosense.com](http://www.geosense.com) e [sales@geosense.com](mailto:sales@geosense.com) t +44(0)1359 270457

Specifications are subject to change without notice and should not be construed as a commitment by Geosense. Geosense assumes no responsibility for any errors that may appear in this document. In no event shall Geosense be liable for incidental or consequential damages arising from the use of this document or the systems described in this document. All Content published or distributed by Geosense is made available for the purposes of general information. You are not permitted to publish our content or make any commercial use of our content without our express written consent. This material or any portion of this material may not be reproduced, duplicated, copied, sold, resold, edited, or modified without our express written consent.